

OEM 9800 Series Print & Apply Applicators



OEM's 9800 Print & Apply Applicators combine the flexibility of thermal transfer printers with the reliability of OEM Applicators. The 9800 is available with interchangeable tamp, vacuum-blow and/or corner wrap applicators. The 9800 is available as a stand alone unit or integrated into a complete system.

Visit OEM's web site
for complete product line



www.oemltd.com

AVAILABLE PRINT ENGINES:

Zebra 170 PAX	203 or 300 dpi resolution, max print width: 6.6", max media width: 7.2", max print speed: 8 ips @ 300 dpi or 12 ips @ 203 dpi.
Sato 8459,8460, 8485,8490	203 or 300 dpi resolution, max print width: 5.0", max media width: 5.25", max print speed: 5 ips @ 300 dpi or 10 ips @ 203 dpi.
Datamax PE-42 PE-43	203 or 300 dpi resolution, max print width: 4.1", max media width: 5.0", max print speed: 8 ips @ 300 dpi or 10 ips @ 203 dpi.

FEATURES:

- Heavy-duty aluminum construction
- Powered waste rewinder
- Easily adjustable supply roll tension clutch
- Universal mounting arm

- Interchangeable applicators (tamp, vacuum-blow corner wrap)
- Easily accessible components
- Quick change print engine (five bolts)
- MADE IN U.S.A

OPTIONS:

- TAMP
- VACUUM-BLOW
- CORNER WRAP
- Right or left handed

- Low label alarm
- Out of label alarm
- T-stand with locking casters
- Additional printer memory

SPECIFICATIONS:

- SUPPLY ROLL SIZE: 12" O.D.
(other sizes optional)
- CORE SIZE: 3" I.D.
(other sizes optional)

- MACHINE DIMENSIONS: 18"W x 22"H x 32"L
(Length will vary slightly due to size of tamp pad)
- POWER REQUIREMENTS: 120 VAC
- AIR REQUIREMENTS: 40-80 PSI; 1-2 CFM
clean, dry, non-oiled



PRESSURE SENSITIVE LABEL DISPENSING EQUIPMENT
• SYSTEMS DESIGN & MANUFACTURING •

OEM LABELING EQUIPMENT

934 Salem Parkway, P.O. Box 830, Salem, OH 44460-0830 U.S.A.

Phone (330) 332-8596 FAX (330) 332-8598

www.oemltd.com oemltd@oemltd.com

Distributed by:

